

Section 1: IDENTIFICATION

Product Name: Natural Gas Liquids
Synonyms: NGL
Product Use: Refinery feedstock.
Restrictions on Use: Not available.
Manufacturer/Supplier: Ovintiv Services Inc.
 500 Centre Street SE
 Calgary, AB T2P 2S5
Phone Number: (403) 645-2000
Emergency Phone: (403) 645-3333
 Canutec: (613) 996-6666 or Cellular *666
Date of Preparation of SDS: November 2, 2020

Section 2: HAZARD(S) IDENTIFICATION
GHS INFORMATION

Classification: Flammable Gases, Category 1
 Gases Under Pressure - Liquefied Gas
 Germ Cell Mutagenicity, Category 1B
 Carcinogenicity, Category 1A
 Reproductive Toxicity, Category 2
 Specific Target Organ Toxicity (Single Exposure), Category 3 - Narcotic Effects
 Specific Target Organ Toxicity (Repeated Exposure), Category 2
 Simple Asphyxiant, Category 1

LABEL ELEMENTS
Hazard
Pictogram(s):

Signal Word: Danger

Hazard
Statements:

Extremely flammable gas.
 Contains gas under pressure; may explode if heated.
 May cause genetic defects.
 May cause cancer.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.
 May displace oxygen and cause rapid suffocation.

Precautionary Statements

Prevention: Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.
 Do not breathe gas.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves, protective clothing and eye protection.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Call a POISON CENTER or doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 In case of leakage, eliminate all ignition sources.

Storage: Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.
 Protect from sunlight.

Disposal: Dispose of contents/container in accordance with applicable regional, national and local laws and regulations.

Hazards Not Otherwise Classified: Not applicable.

Ingredients with Unknown Toxicity: None.

This material is considered hazardous by the OSHA Hazard Communication Standard, (29 CFR 1910.1200). This material is considered hazardous by the Hazardous Products Regulations.

| |
|--|
| Section 3: COMPOSITION / INFORMATION ON INGREDIENTS |
|--|

| Hazardous Ingredient(s) | Common name / Synonyms | CAS No. | % vol./vol. |
|---------------------------------------|---------------------------|------------|-------------|
| Natural gas (petroleum), raw liq. mix | Not available. | 64741-48-6 | 100 |
| Propane | Not available. | 74-98-6 | 10 - 30 |
| Butane | Not available. | 106-97-8 | 10 - 30 |
| Propane, 2-methyl- | Isobutane | 75-28-5 | 10 - 30 |
| Butane, 2-methyl- | Isopentane | 78-78-4 | 7 - 13 |
| Pentane | Not available. | 109-66-0 | 7 - 13 |
| Hexane | Not available. | 110-54-3 | 5 - 10 |
| Heptane | Not available. | 142-82-5 | 3 - 7 |
| Octane | Not available. | 111-65-9 | 1 - 5 |
| Benzene | Not available. | 71-43-2 | 0.1 - 1 |
| Benzene, methyl- | Toluene | 108-88-3 | 0.1 - 1 |
| Benzene, dimethyl- | Xylene | 1330-20-7 | 0.1 - 1 |

| |
|--------------------------------------|
| Section 4: FIRST-AID MEASURES |
|--------------------------------------|

Inhalation: If inhaled: Remove person to fresh air and keep comfortable for breathing.
 Call a poison center or doctor if you feel unwell. If breathing or the heart stops, trained personnel should immediately begin artificial respiration (AR) or cardiopulmonary resuscitation (CPR) respectively. Get medical attention immediately.

Acute and delayed symptoms and effects: May cause drowsiness or dizziness. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness. May displace oxygen and cause rapid suffocation. Central nervous system depression can occur if product is present in concentrations that will reduce the oxygen content of air below 18 % (vol). Symptoms may include headache, lightheadedness, drowsiness, disorientation, vomiting and seizures. Unconsciousness and death may occur with severe oxygen deprivation. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Eye Contact: If in eyes: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

Acute and delayed symptoms and effects: Contact with rapidly expanding or liquefied gas may cause irritation and/or frostbite. The pain after contact with liquid can quickly subside. Permanent eye damage or blindness could result. May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact: Contact with rapidly expanding or liquefied gas may cause irritation and/or frostbite. If on skin: Wash with plenty of water. Get immediate medical advice/attention. Thaw frosted parts with lukewarm water. Do not rub affected area. Remove non-adhering contaminated clothing. Do not remove adherent material or clothing.

Acute and delayed symptoms and effects: Contact with rapidly expanding or liquefied gas may cause irritation and/or frostbite. Symptoms of frostbite include change in skin color to white or grayish-yellow. The pain after contact with liquid can quickly subside. May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: Not a normal route of exposure.

Acute and delayed symptoms and effects: Not a normal route of exposure.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE-FIGHTING MEASURES

FLAMMABILITY AND EXPLOSION INFORMATION

Extremely flammable gas. Contains gas under pressure; may explode if heated. Will be easily ignited by heat, sparks or flames. Will form explosive mixtures with air. Vapors from liquefied gas are initially heavier than air and spread along ground. Vapors may travel to source of ignition and flash back. Cylinders exposed to fire may vent and release flammable gas through

pressure relief devices. Containers may explode when heated. Ruptured cylinders may rocket. **DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.**

If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions.

Fire involving Tanks: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Do not direct water at source of leak or safety devices; icing may occur. Withdraw immediately in case of rising sound from venting safety devices or discoloration of tank. ALWAYS stay away from tanks engulfed in fire. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

Sensitivity to Mechanical Impact: This material is not sensitive to mechanical impact.

Sensitivity to Static Discharge: This material is sensitive to static discharge.

MEANS OF EXTINCTION

Suitable Extinguishing Media: Small Fire: Dry chemical or CO₂.

Large Fire: Water spray or fog. Move containers from fire area if you can do it without risk.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: Oxides of carbon.

Protection of Firefighters: Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources. Vapors may cause dizziness or asphyxiation without warning. Contact with gas or liquefied gas may cause burns, severe injury and/or frostbite. Fire may produce irritating and/or toxic gases. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection. Always wear thermal protective clothing when handling refrigerated/cryogenic liquids.

Section 6: ACCIDENTAL RELEASE MEASURES

Emergency Procedures: As an immediate precautionary measure, isolate spill or leak area for at least 100 meters (330 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Keep out of low areas. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded.

Personal Precautions: Do not touch or walk through spilled material. Use personal protection recommended in Section 8.

Environmental Precautions: Not normally required.

Methods for Containment: Stop leak if you can do it without risk. If possible, turn leaking

containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Do not direct water at spill or source of leak.

Methods for Clean-Up: Prevent spreading of vapors through sewers, ventilation systems and confined areas. Isolate area until gas has dispersed.
CAUTION: When in contact with refrigerated/cryogenic liquids, many materials become brittle and are likely to break without warning.

Other Information: See Section 13 for disposal considerations.

Section 7: HANDLING AND STORAGE

Handling:

Do not breathe gas. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. See Section 8 for information on Personal Protective Equipment.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Store away from incompatible materials. See Section 10 for information on Incompatible Materials. Keep out of the reach of children.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines**Component**

Natural gas (petroleum), raw liq. mix [CAS No. 64741-48-6]

ACGIH: No TLV established.

OSHA: No PEL established.

Propane [CAS No. 74-98-6]

ACGIH: Simple asphyxiant; Explosion hazard

OSHA: 1000 ppm (TWA), 1800 mg/m³ (TWA);

Butane [CAS No. 106-97-8]

ACGIH: 1000 ppm (STEL); Explosion hazard (2012)

OSHA: 800 ppm (TWA) [Vacated];

Isobutane [CAS No. 75-28-5]

ACGIH: 1000 ppm (STEL); Explosion hazard (2012)

OSHA: No PEL established.

Isopentane [CAS No. 78-78-4]

ACGIH: 1000 ppm (TWA); (2013)

OSHA: No PEL established.

SAFETY DATA SHEET

Date of Preparation: November 2, 2020

Pentane [CAS No. 109-66-0]

ACGIH: 1000 ppm (TWA); (2013)**OSHA:** 1000 ppm (TWA), 2950 mg/m³ (TWA);
600 ppm (TWA); 750 ppm (STEL) [Vacated];

Hexane [CAS No. 110-54-3]

ACGIH: 50 ppm (TWA); Skin, BEI (1996)**OSHA:** 500 ppm (TWA), 1800 mg/m³ (TWA); Skin.
50 ppm (TWA) [Vacated];

Heptane [CAS No. 142-82-5]

ACGIH: 400 ppm (TWA); 500 ppm (STEL); (1979)**OSHA:** 500 ppm (TWA), 2000 mg/m³ (TWA);
400 ppm (TWA); 500 ppm (STEL) [Vacated];

Octane [CAS No. 111-65-9]

ACGIH: 300 ppm (TWA); (1979)**OSHA:** 500 ppm (TWA), 2350 mg/m³ (TWA);
300 ppm (TWA); 375 ppm (STEL) [Vacated];

Benzene [CAS No. 71-43-2]

ACGIH: 0.5 ppm (TWA); 2.5 ppm (STEL); Skin; A1; BEI (1996)**OSHA:** 1 ppm (TWA); 5 ppm (STEL);

Toluene [CAS No. 108-88-3]

ACGIH: 20 ppm (TWA); A4; BEI (2006)**OSHA:** 200 ppm (TWA); 300 ppm (C); 500 ppm (Peak) (Maximum duration: 10 minutes.)
100 ppm (TWA); 150 ppm (STEL) [Vacated];

Xylene [CAS No. 1330-20-7]

ACGIH: 100 ppm (TWA); 150 ppm (STEL); A4; BEI (1992)**OSHA:** 100 ppm (TWA), 435 mg/m³ (TWA);
150 ppm (STEL) [Vacated];**PEL:** Permissible Exposure Limit**TLV:** Threshold Limit Value**TWA:** Time-Weighted Average**STEL:** Short-Term Exposure Limit**C:** Ceiling**Engineering Controls:**

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapour, gas, etc.) below recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT (PPE)**Eye/Face Protection:**

Wear cold insulating face shield and eye protection. Use

equipment for eye protection that meets the standards referenced by CSA Standard CAN/CSA-Z94.3-92 and OSHA regulations in 29 CFR 1910.133 for Personal Protective Equipment.

Hand Protection: Wear protective gloves. Wear cold insulating gloves. Consult manufacturer specifications for further information.

Skin and Body Protection: Wear protective clothing.

Respiratory Protection: If engineering controls and ventilation are not sufficient to control exposure to below the allowable limits then an appropriate NIOSH/MSHA approved air-purifying respirator that meets the requirements of CSA Standard CAN/CSA-Z94.4-11, with organic vapor cartridge, or self-contained breathing apparatus must be used. Supplied air breathing apparatus must be used when oxygen concentrations are low or if airborne concentrations exceed the limits of the air-purifying respirators.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices. Consult a competent industrial hygienist to determine hazard potential and/or the PPE manufacturers to ensure adequate protection.

| |
|--|
| Section 9: PHYSICAL AND CHEMICAL PROPERTIES |
|--|

| | |
|--|--------------------------|
| Appearance: | Clear, colourless gas. |
| Colour: | Colourless. |
| Odour: | Hydrocarbon. |
| Odour Threshold: | Not available. |
| Physical State: | Gas. |
| pH: | Not available. |
| Melting Point / Freezing Point: | Not available. |
| Initial Boiling Point: | Not available. |
| Boiling Range: | Not available. |
| Flash Point: | Not available. |
| Evaporation Rate: | Not available. |
| Flammability (solid, gas): | Extremely flammable gas. |
| Lower Flammability Limit: | 1.8 % (Butane) |
| Upper Flammability Limit: | 9.5 % (Propane) |
| Vapor Pressure: | Not available. |

SAFETY DATA SHEET

| | |
|--|----------------------------|
| Vapor Density: | Not available. |
| Relative Density: | Not available. |
| Solubilities: | Slightly soluble in water. |
| Partition Coefficient: n-Octanol/Water: | Not available. |
| Auto-ignition Temperature: | 225 °C (437 °F) (Hexane) |
| Decomposition Temperature: | Not available. |
| Viscosity: | Not available. |
| Percent Volatile, wt. %: | 100 |
| VOC content, wt. %: | Not available. |
| Density: | 732.9 kg/m ³ |
| Coefficient of Water/Oil Distribution: | Not available. |

| |
|---|
| Section 10: STABILITY AND REACTIVITY |
|---|

| | |
|--|---|
| Reactivity: | Contact with incompatible materials. Sources of ignition. Exposure to heat. |
| Chemical Stability: | Stable under normal storage conditions. |
| Possibility of Hazardous Reactions: | None known. |
| Conditions to Avoid: | Contact with incompatible materials. Sources of ignition. Exposure to heat. |
| Incompatible Materials: | Oxidizers. |
| Hazardous Decomposition Products: | Not available. |

| |
|--|
| Section 11: TOXICOLOGICAL INFORMATION |
|--|

EFFECTS OF ACUTE EXPOSURE
Product Toxicity

| | |
|--------------------|----------------|
| Oral: | Not available. |
| Dermal: | Not available. |
| Inhalation: | Not available. |

Component Toxicity

| Component | CAS No. | LD ₅₀ oral | LD ₅₀ dermal | LC ₅₀ |
|---------------------------------------|------------|-----------------------|-------------------------|------------------------------------|
| Natural gas (petroleum), raw liq. mix | 64741-48-6 | Not available. | Not available. | Not available. |
| Propane | 74-98-6 | Not available. | Not available. | Not available. |
| Butane | 106-97-8 | Not available. | Not available. | 658000 mg/m ³ (rat); 4H |

Natural Gas Liquids

Date of Preparation: November 2, 2020

SAFETY DATA SHEET

| | | | | |
|------------|-----------|-------------------|-----------------------|------------------------------------|
| Isobutane | 75-28-5 | Not available. | Not available. | 570000 ppm (rat); 15M |
| Isopentane | 78-78-4 | Not available. | Not available. | Not available. |
| Pentane | 109-66-0 | 400 mg/kg (rat) | Not available. | 364000 mg/m ³ (rat); 4H |
| Hexane | 110-54-3 | 25000 mg/kg (rat) | Not available. | 48000 ppm (rat); 4H |
| Heptane | 142-82-5 | Not available. | Not available. | 103000 mg/m ³ (rat); 4H |
| Octane | 111-65-9 | Not available. | Not available. | 118000 mg/m ³ (rat); 4H |
| Benzene | 71-43-2 | 930 mg/kg (rat) | > 9400 µL/kg (rabbit) | 10000 ppm (rat); 7H |
| Toluene | 108-88-3 | 2600 mg/kg (rat) | 14.1 mL/kg (rabbit) | 49000 mg/m ³ (rat); 4H |
| Xylene | 1330-20-7 | 4300 mg/kg (rat) | > 1700 mg/kg (rabbit) | 5000 ppm (rat); 4H |

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Skin absorption.

Target Organs: Skin. Eyes. Respiratory system. Cardiovascular system. Bone marrow. Liver. Kidneys. Central nervous system. Peripheral nervous system.

Symptoms (including delayed and immediate effects)

Inhalation: May cause drowsiness or dizziness. Excessive inhalation may cause headache, dizziness, confusion, loss of appetite and/or loss of consciousness. May displace oxygen and cause rapid suffocation. Central nervous system depression can occur if product is present in concentrations that will reduce the oxygen content of air below 18 % (vol). Symptoms may include headache, lightheadedness, drowsiness, disorientation, vomiting and seizures. Unconsciousness and death may occur with severe oxygen deprivation. May cause respiratory irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Eye: Contact with rapidly expanding or liquefied gas may cause irritation and/or frostbite. The pain after contact with liquid can quickly subside. Permanent eye damage or blindness could result. May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin: Contact with rapidly expanding or liquefied gas may cause irritation and/or frostbite. Symptoms of frostbite include change in skin color to white or grayish-yellow. The pain after contact with liquid can quickly subside. May cause skin irritation. Signs/symptoms may include localized redness, swelling, and itching.

Ingestion: Not a normal route of exposure.

Skin Sensitization: Not available.

Respiratory Sensitization: Not available.

Medical Conditions Aggravated By Exposure: Not available.

EFFECTS OF CHRONIC EXPOSURE (from short and long-term exposure)

- Target Organs:** Skin. Eyes. Respiratory system. Blood. Cardiovascular system. Bone marrow. Liver. Kidneys. Central nervous system. Peripheral nervous system.
- Chronic Effects:** Hazardous by OSHA/WHMIS criteria. May cause chronic effects. High vapour concentrations, generally greater than 10% by volume, may sensitize the heart and lead to lethal cardiac arrhythmias. Prolonged or repeated inhalation of Isopentane may cause dizziness, weakness, weight loss, anemia, nervousness, pains in the limbs and peripheral numbness. Chronic inhalation of n-Hexane may cause peripheral nerve disorders and central nervous system effects. Reports of chronic poisoning with Benzene, Toluene or Xylene describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Repeated exposure of the eyes to high concentrations of Xylenes vapour may cause reversible eye damage. Chronic inhalation exposure to xylene causes mid-frequency hearing loss in laboratory animals. Xylene reacts synergistically with n-hexane to enhance hearing loss. Immunodepressive effects have also been reported for Benzene.
- Carcinogenicity:** May cause cancer. Chronic exposure to benzene has been associated with an increased incidence of leukemia and multiple myeloma (tumour composed of cells of the type normally found in the bone marrow).

Component Carcinogenicity

| Component | ACGIH | IARC | NTP | OSHA | Prop 65 |
|-----------|-------|---------|-------------|------------------|-------------|
| Benzene | A1 | Group 1 | List 1 | OSHA Carcinogen. | Listed. |
| Toluene | A4 | Group 3 | Not listed. | Not listed. | Not listed. |
| Xylene | A4 | Group 3 | Not listed. | Not listed. | Not listed. |

- Mutagenicity:** May cause genetic defects.
- Reproductive Effects:** Suspected of damaging fertility or the unborn child.
- Developmental Effects**
- Teratogenicity:** Not available.
- Embryotoxicity:** Possible risk of harm to the unborn child. Benzene and Xylene have caused adverse fetal effects in laboratory animals. Exposure to Toluene may affect the developing fetus.
- Toxicologically Synergistic Materials:** Xylene reacts synergistically with n-hexane to enhance hearing loss.

| |
|---|
| Section 12: ECOLOGICAL INFORMATION |
|---|

- Ecotoxicity:** Not available.
- Persistence / Degradability:** Not available.
- Bioaccumulation / Accumulation:** Not available.
- Mobility in Environment:** Not available.

Other Adverse Effects: Not available.**Section 13: DISPOSAL CONSIDERATIONS****Disposal Instructions:** Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.**Section 14: TRANSPORT INFORMATION****U.S. Department of Transportation (DOT)****Proper Shipping Name:** UN1075, PETROLEUM GASES, LIQUEFIED, 2.1**Class:** 2.1**UN Number:** UN1075**Packing Group:** Not applicable.**Label Code:****Canada Transportation of Dangerous Goods (TDG)****Proper Shipping Name:** UN1075, PETROLEUM GASES, LIQUEFIED, 2.1**Class:** 2.1**UN Number:** UN1075**Packing Group:** Not applicable.**Label Code:****Section 15: REGULATORY INFORMATION****Chemical Inventories****US (TSCA)**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Canada (DSL)

The components of this product are in compliance with the chemical notification requirements of the NSN Regulations under CEPA, 1999.

Federal Regulations**United States**

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Natural Gas Liquids

SAFETY DATA SHEET

Date of Preparation: November 2, 2020

SARA Title III

| Component | Section 302 (EHS) TPQ (lbs.) | Section 304 EHS RQ (lbs.) | CERCLA RQ (lbs.) | Section 313 | RCRA CODE | CAA 112(r) TQ (lbs.) |
|------------|------------------------------------|---------------------------------|---------------------|----------------|--------------|------------------------------|
| Propane | Not listed. | Not listed. | Not listed. | Not listed. | Not listed. | 10000 |
| Butane | Not listed. | Not listed. | Not listed. | Not listed. | Not listed. | 10000 |
| Isobutane | Not listed. | Not listed. | Not listed. | Not listed. | Not listed. | 10000 |
| Isopentane | Not listed. | Not listed. | Not listed. | Not listed. | Not listed. | 10000 |
| Pentane | Not listed. | Not listed. | Not listed. | Not listed. | Not listed. | 10000 |
| Hexane | Not listed. | Not listed. | 5000 | 313 | Not listed. | Not listed. |
| Benzene | Not listed. | Not listed. | 10 | 313 | U019 | Not listed. |
| Toluene | Not listed. | Not listed. | 1000 | 313 | U220 | Not listed. |
| Xylene | Not listed. | Not listed. | 100 | 313 | U239 | Not listed. |

State Regulations

Massachusetts

US Massachusetts Commonwealth's Right-to-Know Law (Appendix A to 105 Code of Massachusetts Regulations Section 670.000)

| Component | CAS No. | RTK List |
|------------|-----------|----------|
| Propane | 74-98-6 | Listed. |
| Butane | 106-97-8 | Listed. |
| Isobutane | 75-28-5 | Listed. |
| Isopentane | 78-78-4 | Listed. |
| Pentane | 109-66-0 | Listed. |
| Hexane | 110-54-3 | Listed. |
| Heptane | 142-82-5 | Listed. |
| Octane | 111-65-9 | Listed. |
| Benzene | 71-43-2 | E |
| Toluene | 108-88-3 | Listed. |
| Xylene | 1330-20-7 | Listed. |

Note: E = Extraordinarily Hazardous Substance

New Jersey

US New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

| Component | CAS No. | RTK List |
|------------|-----------|----------|
| Propane | 74-98-6 | SHHS |
| Butane | 106-97-8 | SHHS |
| Isobutane | 75-28-5 | SHHS |
| Isopentane | 78-78-4 | SHHS |
| Pentane | 109-66-0 | SHHS |
| Hexane | 110-54-3 | SHHS |
| Heptane | 142-82-5 | SHHS |
| Octane | 111-65-9 | SHHS |
| Benzene | 71-43-2 | SHHS |
| Toluene | 108-88-3 | SHHS |
| Xylene | 1330-20-7 | SHHS |

Note: SHHS = Special Health Hazard Substance

SAFETY DATA SHEET**Pennsylvania**

US Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

| Component | CAS No. | RTK List |
|------------------|----------------|-----------------|
| Propane | 74-98-6 | Listed. |
| Butane | 106-97-8 | Listed. |
| Isobutane | 75-28-5 | Listed. |
| Isopentane | 78-78-4 | Listed. |
| Pentane | 109-66-0 | Listed. |
| Hexane | 110-54-3 | Listed. |
| Heptane | 142-82-5 | Listed. |
| Octane | 111-65-9 | Listed. |
| Benzene | 71-43-2 | ES |
| Toluene | 108-88-3 | E |
| Xylene | 1330-20-7 | E |

Note: E = Environmental Hazard; S = Special Hazardous Substance**California****California Prop 65:**

WARNING This product can expose you to chemicals including Toluene, Benzene, and Ethylbenzene which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Section 16: OTHER INFORMATION**Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for their own particular use.

Date of Preparation of SDS: November 2, 2020**Version:** 1.0**GHS SDS Prepared by:** Deerfoot Consulting Inc.**Phone:** (403) 720-3700